

DELTA FULL COLOUR LED COLOUR CHANGERS



DELTA is the brightest LED colour changer in its category (**550 Lux at 5 m / Spot lenses**). The DELTA light source is composed of 40 Full Colour LEDs, which can independently generate 16 million colours.

Full Colour technology gives a perfectly uniform light beam, without false and troublesome chromatic separation effects, guaranteeing a fine control over colour temperature.

DELTA is easily installable even in the most refined settings, thanks to the attractive appearance of the LEDs all generating the same colour at the same time.

For each model, **four optical units** that can be easily interchanged by users are available, offering different light beam projection angles (Spot, Medium flood, Wide flood, Very Wide Flood) and optimized for the use of DELTA at different distances from the surfaces to be coloured.

DELTA offers an **IP65 protection rating**, making it suitable for a vast variety of uses, either outdoor or indoor.

DELTA has a **full-range AC 90-260 V, 50-60 Hz power supply**, and therefore ensures reliable operation even in the case of voltage drops. DELTA can be used without external consoles, in chains of up to 32 units.

DELTA 5 offers a range of exclusive functions, including: * **Twilight sensor** for switching the unit on and off automatically, according to external light intensity. The sensitivity of the sensor can be varied by the user, making it particularly suitable for optimising energy savings.

* 3 different colour mixing modes: **RGB, CMY, HSV**.

* Possibility of memorizing a personalized white either from the menu or via DMX.

The white is recalled with the dedicated **DMX "White" channel**. All functions of the internal DELTA menu can be programmed and memorized in a sequence of events (including different luminosity settings, generation of 16 million different colours, special effects, etc.), which can be played back in a predetermined sequence over an entire week.



The Lighting Company



● DELTA FULL COLOUR LED COLOUR CHANGERS

DELTA is available in 2 versions:

DELTA R: exclusive motorized movement of the head on 3 axes; it can operate in vertical, horizontal or inverted positions, and can be positioned on the floor or ground, or fitted to trusses; complete with a practical accessory for anchorage to the ground.
(Pan 320° / Tilt 1 160° / Tilt 2 135°)



DELTA B: designed for fixed installation on walls or trusses; fitted with a swivelling fixing bracket (Pan 115° / Tilt 170°)

DELTA B's head is detachable from the base and can be supplied and controlled by two dedicated rack mountable units, Z40 (for 4 DELTA B heads) and Z20 (for 2 DELTA B heads).

