

MOTOR YOKE 2™

THE UNIVERSAL TOOL TO MOVE ALL LIGHTING FIXTURES

Further increasing the capabilities of lighting professionals world wide, the MotorYoke 2 can now be used for practically any stage or studio fixture up to 40 kg (88 lb).

Absolutely silent and superbly smooth 16 bit pan and tilt motion makes the MOTOR YOKE 2™ the preferred option when requiring the very best quality.

With exact position reproduction and the ability to quietly return to its correct position after having been accidentally moved, the MOTOR YOKE 2™ stands alone when outstanding performance is expected.



MOTOR YOKE 2™ WITH ARRI COMPACT 2500 W HMI, MOTOR FOCUS AND INNO DIM 360™

THE NEW MOTOR YOKE 2™ INCLUDES THESE FEATURES:

- ✓ Horizontal range of motion 364° with a maximum speed of 25 seconds with 16 bit control (2 channels)
- ✓ Vertical range of motion 180° with maximum speed of 14 sec
- ✓ Backlash free worm drive with safety coupling to prevent damage during transport and installation
- ✓ If the programmed position of the spotlight is accidentally shifted the MOTOR YOKE 2™ automatically returns back to position
- ✓ Reproducible precision of the horizontal and vertical position <math><0,1^\circ</math>
- ✓ Total weight of the MOTOR YOKE 2™ with pan and tilt drive only 4,2kg / 9,2lb

The following options are available:

Remote control Iris
Motorized Focus
Motorized Zoom lenses
Color scroller
Inno Dim 170 or 360 dimmer shutters
GAM SX4 with loop effects or the new 6-Gobo Tray

To install the MOTOR YOKE 2™ individually or in multiples we have Control/Power units for 1 and for 6 spotlights. They operate on input power from 85 to 260 VAC 50/60HZ. This permits the unit to be operated worldwide and controlled from modern lighting control consoles suited for DMX 512.

lighting innovation

Hermann Sorger GmbH

Museumstrasse 3b, A-1070 Vienna, Austria

Tel: +43 (1) 5265256, Fax: +43 (1) 5230968

office@lightinginnovation.at

www.lightinginnovation.at

